Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

**IPA** 

Initial release date: 18.12.2002 Revision Date: 04.06.2015

Version 2.1

MSDS Number: 800001000631

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

: IPA Trade name

Product code : S1111, ZA07A

Synonyms : IPA, Isopropanol, Propan-2-ol, Propanol, sec-, Propyl alcohol,

sec-, Dimethyl carbinol

CAS-No. : 67-63-0

Index-No. : 603-117-00-0

EC-No. : 200-661-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-: Industrial Solvent.

stance/Mixture

Recommended restrictions

on use

: Advice in this document relates only to product as originally supplied. Other derivative chemicals will have different proper-

ties and hazards. Advice should be sought on their safe han-

dling and use.

1.3 Details of the supplier of the safety data sheet

Company : Shell Chemicals Europe B.V.

> PO Box 2334 3000 CH Rotterdam

Netherlands

Telephone : +31 (0)10 441 5137 / +31 (0)10 441 5191

Telefax : +31 (0)20 716 8316/ +31 (0)20 713 9230

E-mail address of person

responsible for the SDS

: sccmsds@shell.com

1.4 Emergency telephone number

Emergency telephone num-: +44 (0) 1235 239 670

ber

#### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

# Classification T.R. SEA No 28848

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

1/18 800001000631 TR

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## **IPA**

Initial release date: 18.12.2002 Revision Date: 04.06.2015

Version 2.1

MSDS Number: 800001000631

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Narcotic effects.

H336: May cause drowsiness or dizziness.

Classification T.R. SAE No 27092

Highly flammable R11: Highly flammable.

Irritant R36: Irritating to eyes.

R67: Vapours may cause drowsiness and dizzi-

ness.

#### 2.2 Label elements

### Labelling T.R. SEA No 28848

Hazard pictograms





Signal word : Danger

Hazard statements : PHYSICAL HAZARDS:

H225 Highly flammable liquid and vapour.

**HEALTH HAZARDS:** 

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
ENVIRONMENTAL HAZARDS:

Not classified as environmental hazard

according to CLP criteria.

Precautionary statements : Prevention:

P210 Keep away from heat/sparks/open

flames/hot surfaces. - No smoking.

P243 Take precautionary measures against static

discharge.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with wa-

ter for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P304 + P340 IF INHALED: Remove person to fresh air

and keep comfortable for breathing.

Disposal:

P501 Dispose of contents and container to ap-

propriate waste site or reclaimer in accordance with local and national regulations.

2 / 18 800001000631 TR

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## **IPA**

Initial release date: 18.12.2002 Revision Date: 04.06.2015

Version 2.1

MSDS Number: 800001000631

#### 2.3 Other hazards

Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition sources causing a flashback fire danger.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable airvapour mixtures can occur.

Slightly irritating to respiratory system.

# **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Substance name : Isopropyl alcohol, 67-63-0

Index-No. : 603-117-00-0

### **Hazardous components**

Chemical Name	CAS-No. EC-No. Registration number	T.R. SAE No 27092	T.R. SEA No 28848	Concentration (%)
Isopropyl alcohol	67-63-0 200-661-7	F; R11 Xi; R36 R67	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336	100

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice In general no treatment is necessary, however, obtain medical

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

: Remove to fresh air. If rapid recovery does not occur, trans-If inhaled

port to nearest medical facility for additional treatment.

In case of skin contact : Remove contaminated clothing. Flush exposed area with wa-

> ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

In case of eye contact : Immediately flush eyes with large amounts of water for at least

15 minutes while holding eyelids open. Transport to the near-

3/18 800001000631

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

**IPA** 

Initial release date: 18.12.2002 Revision Date: 04.06.2015

Version 2.1

MSDS Number: 800001000631

est medical facility for additional treatment.

If swallowed : If swallowed, do not induce vomiting: transport to nearest

medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

# 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : If material enters lungs, signs and symptoms may include

coughing, choking, wheezing, difficulty in breathing, chest

congestion, shortness of breath, and/or fever.

Eye irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blurred vision.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Potential for chemical pneumonitis.

Call a doctor or poison control center for guidance.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical

powder, carbon dioxide, sand or earth may be used for small

fires only.

Unsuitable extinguishing

media

: None

# 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Carbon monoxide may be evolved if incomplete combustion

occurs.

### 5.3 Advice for firefighters

Special protective equipment

for firefighters

: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing me- : Standard procedure for chemical fires.

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## **IPA**

Initial release date: 18.12.2002 Revision Date: 04.06.2015

Version 2.1

MSDS Number: 800001000631

thods

Further information : Clear fire area of all non-emergency personnel.

Keep adjacent containers cool by spraying with water.

### **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

: Observe the relevant local and international regulations Personal precautions

Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Vapour may form an explosive mixture with air. Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unpro-

tected personnel.

Stay upwind and keep out of low areas.

#### 6.2 Environmental precautions

**Environmental precautions** 

: Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bond-

ing and grounding (earthing) all equipment. Ventilate contaminated area thoroughly. Monitor area with combustible gas indicator.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up

: For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely Remove contaminated soil and dispose of safely.

5/18 800001000631

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## **IPA**

Initial release date: 18.12.2002 Revision Date: 04.06.2015

Version 2.1

MSDS Number: 800001000631

#### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

# **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Technical measures : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Chapter 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

material.

Ensure that all local regulations regarding handling and sto-

rage facilities are followed.

Advice on safe handling : Avoid contact with skin, eyes and clothing.

Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Advice on protection against

fire and explosion

: Bulk storage tanks should be diked (bunded). Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Do NOT use compressed air for filling, discharging, or han-

dling operations.

Hygiene measures : Read in conjunction with the Exposure Scenario for your spe-

cific use contained in the Annex.

Wash hands before eating, drinking, smoking and using the

toilet. Launder contaminated clothing before re-use.

# 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: The vapour is heavier than air. Beware of accumulation in pits and confined spaces. Refer to section 15 for any additional specific legislation covering the packaging and storage of this

product.

Packaging material : Suitable material: For containers, or container linings use mild

steel, stainless steel.

Unsuitable material: Natural, butyl, neoprene or nitrile rubbers.

#### 7.3 Specific end use(s)

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## **IPA**

Initial release date: 18.12.2002 Revision Date: 04.06.2015

Version 2.1

MSDS Number: 800001000631

Specific use(s)

: Please refer to Ch16 and/or the annexes for the registered uses under REACH.

Ensure that all local regulations regarding handling and sto-

rage facilities are followed.

See additional references that provide safe handling practices: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices

on Static Electricity).

CENELEC CLC/TR 50404 (Electrostatics – Code of practice

for the avoidance of hazards due to static electricity).

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Isopropyl alcohol	67-63-0	MAC	200 ppm 500 mg/m3	TR OEL

### **Biological occupational exposure limits**

No biological limit allocated.

## 8.2 Exposure controls

## **Engineering measures**

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure quidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## **IPA**

Initial release date: 18.12.2002 Revision Date: 04.06.2015

Version 2.1

MSDS Number: 800001000631

Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle.

## Personal protective equipment

Eye protection : Wear goggles for use against liquids and gas.

Wear full face shield if splashes are likely to occur.

Hand protection

Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Butyl rubber. Nitrile rubber. Incidental contact/Splash protection: PVC or neoprene rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection

: Wear antistatic and flame retardant clothing if a local risk assessment deems it so.

Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing

over parts of the body subject to exposure.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.

and provide employee skin care pro

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropri-

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

# **IPA**

Initial release date: 18.12.2002 Revision Date: 04.06.2015

e: 04.06.2015 Version 2.1

MSDS Number: 800001000631

ate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [boiling

point >65 °C (149 °F)].

Protective measures : Personal protective equipment (PPE) should meet recom-

mended national standards. Check with PPE suppliers.

#### **Environmental exposure controls**

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local envi-

ronmental legislation.

Information on accidental release measures are to be found in

section 6.

# **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Appearance : Liquid.

Colour : clear

Odour : characteristic

Odour Threshold : Data not available

pH : Not applicable

Melting point/freezing point : -88 °C

Boiling point/boiling range : 82 - 83 °C

Flash point : 12 °C

Method: Abel

Evaporation rate : 1,5

Method: ASTM D 3539, nBuAc=1

Flammability (solid, gas) : Not applicable

Upper explosion limit : upper flammability limit

12 %(V)

Lower explosion limit : lower flammability limit

2 %(V)

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

# **IPA**

Initial release date: 18.12.2002 Revision Date: 04.06.2015

Version 2.1

MSDS Number: 800001000631

Vapour pressure : 6,020 Pa (20 °C)

Relative vapour density : 2 (20 °C)

Relative density : 0,78 - 0,79 (20 °C)

Density : 785 - 786 kg/m3 (20 °C)

Method: ASTM D4052

Solubility(ies)

Water solubility : completely miscible

Solubility in other solvents : Readily soluble in various organic solvents.

Partition coefficient: n-

octanol/water

: log Pow: 0,05

Auto-ignition temperature : 425 °C

Method: ASTM D-2155

Decomposition temperature : Not applicable

Viscosity

Viscosity, dynamic : 2,43 mPa.s

Viscosity, kinematic : Data not available

Explosive properties : Classification Code: Not classified

Oxidizing properties : Not applicable

9.2 Other information

Surface tension : 22,7 mN/m, 20 °C

Conductivity: > 10 000 pS/m, A number of factors,

for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be a static accumu-

lator.

Molecular weight : 60,1 g/mol

10 / 18 800001000631 TR

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## **IPA**

Initial release date: 18.12.2002 Revision Date: 04.06.2015

Version 2.1

MSDS Number: 800001000631

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

### 10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

#### 10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

Prevent vapour accumulation.

In certain circumstances product can ignite due to static elec-

tricity.

## 10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

### 10.6 Hazardous decomposition products

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

# SECTION 11: Toxicological information

## 11.1 Information on toxicological effects

Information on likely routes of : Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

### **Acute toxicity**

### **Product:**

exposure

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Remarks: Low toxicity:

Acute inhalation toxicity : Remarks: Low toxicity by inhalation.

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Remarks: Low toxicity:

### Skin corrosion/irritation

#### Product:

11 / 18 800001000631 TR

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

# **IPA**

Initial release date: 18.12.2002 Revision Date: 04.06.2015

Version 2.1

MSDS Number: 800001000631

Remarks: Not irritating to skin.

## Serious eye damage/eye irritation

### **Product:**

Remarks: Causes serious eye irritation.

### Respiratory or skin sensitisation

### **Product:**

Remarks: Not expected to be a sensitiser.

### Germ cell mutagenicity

# **Product:**

Genotoxicity in vivo : Remarks: Not mutagenic.

## Carcinogenicity

### **Product:**

Remarks: Not a carcinogen.

Material	GHS/CLP Carcinogenicity Classification
Isopropyl alcohol	No carcinogenicity classification.

### Reproductive toxicity

# **Product:**

Effects on fertility

Remarks: Does not impair fertility. Not a developmental toxicant.

## STOT - single exposure

# **Product:**

Remarks: May cause drowsiness and dizziness.

### STOT - repeated exposure

# **Product:**

Remarks: Kidney: caused kidney effects in male rats which are not considered relevant to humans

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## **IPA**

Initial release date: 18.12.2002 Revision Date: 04.06.2015

Version 2.1

MSDS Number: 800001000631

# **Aspiration toxicity**

### **Product:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

#### **Further information**

## **Product:**

Remarks: Exposure may enhance the toxicity of other materials.

Classifications by other authorities under varying regulatory frameworks may exist.

# **SECTION 12: Ecological information**

# 12.1 Toxicity

## **Product:**

Toxicity to fish (Acute toxic-

ity)

: Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

Toxicity to daphnia and other : Remarks: Practically non toxic: aquatic invertebrates (Acute

toxicity)

LL/EL/IL50 > 100 mg/l

Toxicity to algae (Acute toxic-

ity)

: Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

ity)

Toxicity to fish (Chronic toxic- : Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

: Remarks: Data not available

Toxicity to bacteria (Acute

toxicity)

Remarks: Practically non toxic:

LL/EL/IL50 > 100 mg/l

#### 12.2 Persistence and degradability

### **Product:**

: Remarks: Readily biodegradable. Biodegradability

Oxidises rapidly by photo-chemical reactions in air.

### 12.3 Bioaccumulative potential

#### **Product:**

Bioaccumulation : Remarks: Not expected to bioaccumulate significantly.

13 / 18 800001000631 TR

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## **IPA**

Initial release date: 18.12.2002 Revision Date: 04.06.2015

Version 2.1

MSDS Number: 800001000631

### 12.4 Mobility in soil

## **Product:**

Mobility : Remarks: Dissolves in water., If the product enters soil, one or

more constituents will or may be mobile and may contaminate

groundwater.

### 12.5 Results of PBT and vPvB assessment

### **Product:**

Assessment : The substance does not fulfill all screening criteria for persis-

tence, bioaccumulation and toxicity and hence is not consi-

dered to be PBT or vPvB..

#### 12.6 Other adverse effects

### **Product:**

Additional ecological informa: Remarks: Not expected to have ozone depletion potential.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal me-

thods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses

Waste product should not be allowed to contaminate soil or

water.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or na-

tional requirements and must be complied with.

Contaminated packaging Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard. Do not, puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer.

# **SECTION 14: Transport information**

#### 14.1 UN number

14 / 18 800001000631

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

# **IPA**

Initial release date: 18.12.2002 Revision Date: 04.06.2015

Version 2.1

MSDS Number: 800001000631

ADR : UN 1219
RID : UN 1219
IMDG : UN 1219
IATA : UN 1219

# 14.2 UN proper shipping name

ADR : ISOPROPANOL RID : ISOPROPANOL IMDG : ISOPROPANOL IATA : ISOPROPANOL

# 14.3 Transport hazard class(es)

ADR : 3
RID : 3
IMDG : 3
IATA : 3

# 14.4 Packing group

# ADR

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

### RID

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

#### **IMDG**

Packing group : II Labels : 3

Packing group : II Labels : 3

## 14.5 Environmental hazards

#### **ADR**

Environmentally hazardous : no

RID

Environmentally hazardous : no

**IMDG** 

Marine pollutant : no

# 14.6 Special precautions for user

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

**IPA** 

Initial release date: 18.12.2002 Revision Date: 04.06.2015

Version 2.1

MSDS Number: 800001000631

Remarks : Special Precautions: Refer to Chapter 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category : Z Ship type : 2

Product name : Isopropyl alcohol

**Additional Information**: This product may be transported under nitrogen blanketing.

Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined

space entry.

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : The regulatory information is not intended to be comprehen-

sive. Other regulations may apply to this material.

Regulations on the health and safety precautions for chemicals in the workplace. Regulations on the fire protection of buildings. Regulations on the prevention of industrial acci-

dents and the reduction of their effects.

The components of this product are reported in the following inventories:

AICS : Listed

DSL : Listed

IECSC : Listed

ENCS : Listed

KECI : Listed

NZIoC : Listed

PICCS : Listed

EINECS : Listed

16 / 18 800001000631 TR

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## **IPA**

Initial release date: 18.12.2002 Revision Date: 04.06.2015

Version 2.1

MSDS Number: 800001000631

TSCA : Listed

### **SECTION 16: Other information**

**SDS Author** 

Name, Surname : Eda Demirer

Address : Shell & Turcas Petrol A.Ş. Derince Tesisleri

Deniz Mah. P.O Cad. 41900 Derince-Kocaeli

Certified Qualification date : 25 May 2015

Certificate number : GBF-1921

**Further information** 

Training advice : Provide adequate information, instruction and training for op-

erators.

Other information : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Revision changes: Revised according to regulation on Safety Data Sheets (SDSs) regarding hazardous substances and

mixtures (R.G. 13/12/2014-29204)

Sources of key data used to compile the Safety Data

Sheet

 The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

TR / EN

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

**IPA** 

Initial release date: 18.12.2002 Revision Date: 04.06.2015

Version 2.1

MSDS Number: 800001000631